

Solstice® yf Refrigerant (R-1234yf)

Packaging Range: *Americas*

10 lb Disposable* Cylinder



10 lb Returnable Cylinder



Service Can



Valve

1 Valve
Invert for liquid



1 Valve with
2 hand wheels
Red = Liquid
Blue = Gas



Self Sealing Can Valve
Compliant with Section
608 of the EPA CAA
Depressor Can Tap
required



Outlet Connection



SAE J2888 Standard Fitting
CGA 166, left handed threads
0.500 inch (12.7 mm) connection
ACME, 16 threads per inch



SAE J2888 Standard
1/2 inch Acme
Left Hand Threads
No cutback



Features

- Liquid and vapor phase
- Embedded anti-filling valve
- Anti-tamper protection
- Lightweight, open handles for easier access to valve

- Pressure Relief Device
Safety built in
- Reduced Inventory Cost
8 ounce per can, 4 Cans
per case
- Technical support with
scannable QR code



Specifications

	10 lb Disposable	10 lb Returnable	Service Can
Full Cylinder SKU	10616573	10617229	10653369
Nominal Fill Weight	10 lb	10 lb	8 ounce (226 g)
Units per Pallet	60	40	504
Units per Truck	1,320	880	11,088
Net Gas per Truck Load	13,200	8,800	5,544
Certification	US DOT 39	DOT 4BW / TC 4BW	DOT-SP 10232
Unit Dimensions	7.5" x 14.3" (Dia x Tall)	8.7" x 13.5" (Dia x Tall)	3" x 4.8" (Dia x Tall)

* Disposable cylinders cannot be used in Canada.
Pictures are not to scale.

Packaging Range: Americas

100 lb Disposable* Cylinder



950 lb Returnable Cylinder



Bulk Trailer



ISO Container



Valve

1 Valve with
2 hand wheels
Red = Liquid
Blue = Gas



1 Liquid Valve,
Red hand wheel

1 Gas Valve,
Blue hand wheel



Outlet Connection



CGA 670, left handed threads
1.030 inch (26.2 mm) connection
NGO, 14 threads per inch



Chassis w/ Pump



Features

- Liquid and vapor phase
- Anti-tamper protection
- Embedded anti-filling valve
- Dedicated connections and colors

Specifications

	100 lb Disposable	950 lb Returnable	ISO Container	Bulk Trailer
Full Cylinder SKU	10616554	10616558	10581428	10640949
Nominal Fill Weight	100 lb	950 lbs	33,000 lbs / 15,000 kg	40,000 lbs / 18,000 kg
Units per Pallet	Up to 8	Single Cylinder	N/A	N/A
Units per Truck	144	18	1	1
Net Gas per Truck Load	14,400	17100	Partial heel remains in bulk delivery vessels	
Certification	DOT 4BW / TC 4BW	DOT 4BW / TC 4BW	US DOT / UN / IMDG	US DOT
Unit Dimensions	10" x 54" (Dia x Tall)	29.4" x 58" (Dia x Tall)	238" x 96" x 102" (LxWxH)	238" x 96" x 102" (LxWxH)

For more information:



www.1234yfraining.com



www.honeywell-refrigerants.com

Although Honeywell International Inc. believes that the information contained herein is accurate and reliable, it is presented without guarantee or responsibility of any kind and does not constitute any representation or warranty of Honeywell International Inc., either expressed or implied. A number of factors may affect the performance of any products used in conjunction with user's materials, such as other raw materials, application, formulation, environmental factors and manufacturing conditions among others, all of which must be taken into account by the user in producing or using the products. The user should not assume that all necessary data for the proper evaluation of these products are contained herein. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liabilities (including, but not limited to, risks relating to results, patent infringement, regulatory compliance and health, safety and environment) related to the use of the products and/or information contained herein.

Honeywell Refrigerants

115 Tabor Road
Morris Plains, NJ 07950
Phone: 1-800-522-8001



1593 FP Ref v4 | December 2017
© 2017 Honeywell International Inc. All rights reserved.

Honeywell